





















## Product Overview Power entry modules without line filter

www.schurter.com/en/pg05














	Type	Mounting method Side	Plug Outlet	Terminals	Protection class			
<b>Rated Current AC max IEC   UL: 2.5 A   2.5 A</b>								
	<b>CMF1, CMF4</b> IEC Appliance Inlet C8 with Line Switch 1-pole	Screw Rear Side	C8 -	PCB	IP40			
	<b>CMF2, CMF5</b> IEC Appliance Inlet C8 polarized with Line Switch 1-pole	Snap-in or screw-on Rear Side	C8p -	PCB	IP40			
	<b>CMF3, CMF6</b> IEC Appliance Inlet C6 with Line Switch 1-pole	Snap-in or screw-on Rear Side	C6 -	PCB	IP40			
<b>Rated Current AC max IEC   UL: 10 A   6 A</b>								
	<b>8842/8843</b> IEC Appliance Inlet C14 with Fuseholder 2-pole	Screw Front Side	C14 C18 -	Quick-Connect	IP40			• •
<b>Rated Current AC max IEC   UL: 10 A   10 A</b>								
	<b>DD11</b> IEC Appliance Inlet C14 with Line Switch 2-pole, Fuseholder 1- or 2-pole	Screw Front-/Rear-Side	C14 -	Quick-Connect	IP40			• • •
	<b>DD21</b> IEC Appliance Inlet C14 with Line Switch 2-pole, Fuseholder 1- or 2-pole, for PCB mounting,	Screw Rear Side	C14 -	PCB	IP40			• • •
	<b>KEB1</b> IEC Appliance Inlet C14 with Line Switch 1-pole	Snap-in or screw-on Front-/Rear-Side	C14 -	Quick-Connect	IP40			
	<b>KM</b> IEC Appliance Inlet C14 or C18 with Fuseholder 2-pole, Line Switch 1- or 2-pole	Snap-in Front Side	C14 C18 -	Quick-Connect	IP40			• •
	<b>KD</b> IEC Appliance Inlet C14 with Fuseholder 1- or 2-pole, Line Switch 2-pole and Voltage Selector	Snap-in or screw-on Front-/Rear-Side	C14 -	Quick-Connect	IP40			• • •











Power entry modules without line filter (PG05)

	Type	Mounting method Side	Plug Outlet	Terminals	Protection class	V-Lock 		
	<b>KG</b> IEC Appliance Inlet C14 with Fuseholder 1- or 2-pole, Line Switch 2-pole and Voltage Selector	Snap-in or screw-on Front-/Rear-Side	C14 -	Quick-Connect	IP40	•	•	•
	<b>6765</b> IEC Appliance Inlet C14 or C18 with Line Switch 2 pole and Fuseholder 1- or 2-pole	Screw Front-/Rear-Side	C14 C18 -	Solder or Quick-Connect	IP20	•		
	<b>6762</b> IEC Appliance Inlet C14 or C18 with Line Switch 1- or 2-pole and Fuseholder 1-pole	Snap-in or screw-on Front Side	C14 C18 -	Solder or Quick-Connect	IP40	•		
	<b>KP (Outlet)</b> IEC Appliance Inlet C14 with Appliance Outlet F	Sandwich -	C14 F	PCB	IP40			
	<b>KP (FH)</b> IEC Appliance Inlet C14 with Fuseholder 1- or 2-pole (5x20 mm)	Sandwich -	C14 -	PCB	IP40	•	•	•
	<b>Felcom 64</b> IEC Appliance Inlet C14 with modular extended Components	Snap-in Front Side	C14 F	Solder or Quick-Connect	-	•	•	
	<b>6250 / 6255</b> IEC Appliance Inlet C14 with Fuseholder 1- or 2-pole, mates to Felcom	Snap-in Front Side	C14 -	Solder	IP40	•	•	
	<b>GSF1</b> IEC Appliance Inlet C14 with Fuseholder 1- or 2-pole	Sandwich -	C14 -	PCB	IP40	•	•	
	<b>GSF2</b> IEC Appliance Inlet C14 with Fuseholder 1- or 2-pole	Snap-in Front Side	C14 C18 -	Quick-Connect	IP40	•	•	
	<b>KEA</b> IEC Appliance Inlet C14 with Fuseholder 1- or 2-pole	Snap-in or screw-on Front-/Rear-Side	C14 C18 -	Quick-Connect	IP40	•	•	•







Power entry modules without line filter (PG05)

	Type	Mounting method Side	Plug Outlet	Terminals	Protection class	
	<b>KEA-Print</b> IEC Appliance Inlet C14 with Fuseholder 1- or 2-pole for PCB	Snap-in or screw-on Front-/Rear-Side	C14 C18 -	PCB	IP40	• • •
	<b>6200</b> IEC Appliance Inlet C14 with Fuseholder 1-pole, wired	Snap-in or screw-on Front-/Rear-Side	C14 -	Solder or Quick-Connect	IP40	• •
	<b>6202</b> IEC Appliance Inlet C18 with Fuseholder 1-pole	Snap-in or screw-on Front-/Rear-Side	C18 -	Solder or Quick-Connect	IP40	• •
	<b>6205</b> IEC Appliance Inlet C14 with Fuseholder 1-pole, unwired	Snap-in or screw-on Front-/Rear-Side	C14 -	Solder or Quick-Connect	IP40	• •
	<b>1062</b> IEC Appliance Inlet C14 with Fuseholder 1- or 2-pole	Screw Front Side	C14 -	Solder or Quick-Connect	IP20	•
	<b>1064</b> IEC Appliance Inlet C14 or C18 with Fuseholder 1- or 2-pole	Snap-in Front Side	C14 C18 -	Solder or Quick-Connect	IP20	•
	<b>6220</b> IEC Appliance Inlet C14 with Fuseholder 2-pole	Snap-in or screw-on Front-/Rear-Side	C14 -	Solder or Quick-Connect	IP40	• •
	<b>4707</b> IEC Appliance Inlet C14 or C18 with Fuseholder 1- or 2-pole	Screw Front-/Rear-Side	C14 C18 -	Solder or Quick-Connect	IP40	• • •
	<b>4719</b> IEC Appliance Outlet F Shuttered with Fuseholder 1-pole	Snap-in Front Side	- F	Solder	IP40	• •
	<b>KE</b> IEC Appliance Inlet C14 with Fuseholder 1- or 2-pole and Voltage Selector	Snap-in or screw-on Front-/Rear-Side	C14 -	Quick-Connect	IP40	• • •

Power entry modules without line filter (PG05)

	Type	Mounting method Side	Plug Outlet	Terminals	Protection class	V-Lock 		
	<b>6250_6255</b> IEC Appliance Inlet C14 with Fuseholder 1- or 2-pole, mates to Felcom	Snap-in Front Side	C14 -	Solder	IP 40			•
<b>Rated Current AC max IEC   UL: 10 A   13 A</b>								
	<b>KEC</b> IEC Appliance Inlet C14 with Fuseholder 1- or 2-pole and Voltage Selector	Snap-in or screw-on Front-/Rear-Side	C14 -	Quick-Connect	IP40		•	•
<b>Rated Current AC max IEC   UL: 10 A   15 A</b>								
 <small>new</small>	<b>DG11</b> IEC Appliance Inlet C14 or C18 with Circuit Breaker TA35 2-pole	Snap-in or screw-on Front-/Rear-Side	C14 C18 -	Quick-Connect	IP40 or IP67		•	
	<b>DC11</b> IEC Appliance Inlet C14 or C18 with Line Switch 1- or 2-pole	Snap-in or screw-on Front-/Rear-Side	C14 C18 -	Quick-Connect	IP40		•	•
	<b>KEB2</b> IEC Appliance Inlet C14 with Line Switch 2-pole	Snap-in or screw-on Front-/Rear-Side	C14 -	Quick-Connect	IP40			
	<b>DC21</b> IEC Appliance Inlet C14 with Line Switch 2-pole	Screw Rear Side	C14 -	PCB	IP40		•	
	<b>KP (Switch)</b> IEC Appliance Inlet C14 with Line Switch 1- or 2-pole	Sandwich -	C14 -	PCB	IP40		•	
	<b>6050</b> Line Switch, fits to Felcom	Snap-in Front Side	- -	Solder	IP40			
	<b>6135</b> IEC Appliance Inlet C14 with Circuit Breaker TA35 2-pole	Snap-in Front Side	C14 -	Quick-Connect	IP 40		•	

Power entry modules without line filter (PG05)

	Type	Mounting method Side	Plug Outlet	Terminals	Protection class	V-Lock 		
	<b>6145</b> IEC Appliance Inlet C14 with Circuit Breaker TA45	Screw Front Side	C14 -	Quick-Connect	IP 40			
	<b>DF11</b> IEC Appliance Inlet C14 or C18 with recessed Circuit Breaker TA45	Snap-in or screw-on Front-/Rear-Side	C14 C18 -	Quick-Connect	IP 40	•		
<b>Rated Current AC max IEC   UL: 16 A   20 A</b>								
	<b>EC11</b> IEC Appliance Inlet C20 with Line Switch, 2-pole	Snap-in or screw-on Front-/Rear-Side	C20 -	Quick-Connect	IP40	•	•	
	<b>6136</b> IEC Appliance Inlet C20 with Circuit Breaker TA35 1-pole	Snap-in or screw-on Front Side	C20 -	Quick-Connect	IP 40	•		
	<b>EF11</b> IEC Appliance Inlet C20 with Circuit Breaker TA45	Snap-in or screw-on Front-/Rear-Side	C20 -	Quick-Connect	IP 40	•		